



HEXOL SYNLIN SPRINTPLUS 5W30

MOTOR OIL

PRODUCT DESCRIPTION

Hexol Synline SprintPlus 5W30 is an extra high performance, fuel saving, state of art synthetic engine oil. It is produced from high quality synthetic base oils and a complex additive system, ensuring excellent flow characteristics. This product meets the requirements of a wide range of performance levels of engine manufacturers such as: Mercedes Benz, Ford, Toyota, Fiat, BMW, Hyundai, Renault, Porsche, VW, Opel, together with the most stringent US and European specifications for naturally aspirated or turbocharged, gasoline or diesel, passenger cars and light commercial vehicle engine oils.

PERFORMANCE FEATURES

- Exceeds API service SN/CF, ACEA A3/B4 requirements;
- Meets standards imposed by auto makers such Renault RN0700, Renault RN0710, Porsche A40, VW 502 00/504 00/505 00, BMW Longlife – 04, Fiat 9.55535-G1 ;
- Provides reliable start-up and operation even at extremely low temperatures;
- Increases engine life;
- Extremely long oil drain interval;
- Excellent thermal and oxidation stability;
- This oil maintains its properties for up to 5 years when in its original container, sealed, and stored away from any heat source and direct sunlight (storage temperature max. 40°C).

APPLICATION

- Suitable for passenger cars, vans and light commercial vehicles equipped with naturally aspirated or turbo-charged gasoline or diesel engines for which the manufacturer recommends an oil with the above mentioned properties;
- The drain interval will be according to the engine manufacturer's indications.

PROPERTIES

Viscosity Grade SAE	5W30
Density at 15°C [kg/m ³]	850
Kinematic Viscosity at 100°C [mm ² /s]	9.3 - 12.5
Viscosity Index, min	150
Flash Point [°C]min	220
Pour Point [°C]max	-33

PACKAGING

☐ 0.4Kg	☐ 1Kg	☐ 4Kg	☐ 15Kg	☐ 180Kg	☒ 1L	☐ 3L
☐ 0.23L	☐ 0.45L	☐ 0.5L	☐ 0.6L	☐ 0.9L	☒ 208L	☒ 1000L
☒ 4L	☒ 5L	☒ 10L	☒ 20L	☒ 60L		