



## HEXOL SYNLINE ULTRADIESEL DPF 5W30

MOTOR OIL

### PRODUCT DESCRIPTION

Hexol Synline UltraDiesel DPF 5w30 is an extra high performance, low SAPS, fuel saving, synthetic engine oil assuring long drain intervals. Produced from synthetic base oils and a complex additive system, it ensures excellent flow characteristics. Recommended to be used in the most advanced diesel or gasoline, naturally aspirated or turbocharged engines, including "Pumpe-Düse" (PD), fitted with or without diesel particulate filters (DPF) or three-way catalysts. This oil exceeds requirements of the most important European and US automobile associations and engine manufacturers such as: Renault, Mercedes, Peugeot, Volkswagen, Fiat, Opel, Citroen, BMW, Ford, Toyota, Hyundai and others.

### PERFORMANCE FEATURES

- Exceeds ACEA C3-12, ACEA A3/B4-04, API Service CF/SN and CF/SM requirements,
- Meets standard requirements imposed by renowned automakers such as BMW Longlife-04, VW 504.00/507.00, Porche C30, Fiat 9.55535-S2, MB 229.51 and many others,
- Extra long oil drain interval,
- Extra high performance oil providing long engine life,
- Provides reliable start-up and operation even at extremely low temperatures,
- Low SAPS lubricant, guarantees a long lifetime of exhaust gas treatment devices,
- This oil maintains its properties for up to 5 years when in its original container, sealed, and stored away from any heat source and direct sunlight (storage temperature max. 40°C).

### APPLICATION

- Suitable for personal cars, vans and light commercial vehicles equipped with naturally aspirated or turbocharged, including "Pumpe-Düse" (PD), diesel or gasoline engines, fitted with or without Diesel Particulate Filters (DPF) or three-way catalysts, where the manufacturer recommends oil with the above listed properties,
- It has a long drain interval, depending on the engine manufacturer's recommendation.

### PROPERTIES

|                                                   |           |
|---------------------------------------------------|-----------|
| Viscosity Grade SAE                               | 5W30      |
| Density at 15°C [kg/m <sup>3</sup> ]              | 840 – 870 |
| Kinematic Viscosity at 100°C [mm <sup>2</sup> /s] | 9.3-12.5  |
| Viscosity Index, min                              | 150       |
| Flash Point [°C ]min                              | 220       |
| Pour Point [°C ]max                               | -33       |

### PACKAGING

|                                        |                                        |                                         |                                         |                                         |                                          |                                           |
|----------------------------------------|----------------------------------------|-----------------------------------------|-----------------------------------------|-----------------------------------------|------------------------------------------|-------------------------------------------|
| <input type="checkbox"/> 0.4Kg         | <input type="checkbox"/> 1Kg           | <input type="checkbox"/> 4Kg            | <input type="checkbox"/> 15Kg           | <input type="checkbox"/> 180Kg          |                                          |                                           |
| <input type="checkbox"/> 0.23L         | <input type="checkbox"/> 0.45L         | <input type="checkbox"/> 0.5L           | <input type="checkbox"/> 0.6L           | <input type="checkbox"/> 0.9L           | <input checked="" type="checkbox"/> 1L   | <input type="checkbox"/> 3L               |
| <input checked="" type="checkbox"/> 4L | <input checked="" type="checkbox"/> 5L | <input checked="" type="checkbox"/> 10L | <input checked="" type="checkbox"/> 20L | <input checked="" type="checkbox"/> 60L | <input checked="" type="checkbox"/> 208L | <input checked="" type="checkbox"/> 1000L |